



Holding and Fixturing

Neodymium Iron Boron Assemblies

Puritan Neodymium Iron Boron Pot Magnets deliver large holding powers in small packages. These magnets are designed to be “Low Profile, “ but still incorporate a tapped hole in the back wall for mounting.

The Rare Earth Magnets not only have a potent attraction while in direct contact with a work piece, but they also have excellent field projection capabilities.

NEODYMIUM with higher operating Temperatures are available in these Pot Magnets. Samarium Cobalt and Stainless shells and shields are also manufactured. The all Stainless Pot Magnets, for both Alnico and Neodymium, are a level I or II food grade unit.

All Puritan Pot Magnets are Centerless Ground after pressing to ± 0.003 ". The standard tolerance on the lengths is ± 0.010 ". Tighter tolerances are available upon request.

Stocked Sizes

CAT. NO.	Dia. ± 0.003	Length ± 0.010	Tap Style	Tap Depth (inch)	*Maximum Holding Power (lbs.)
NMH3750	3/8	1/2	8 - 32	0.085	5
NMH5050	1/2	1/2	10 - 32	0.15	15
NMH6250	5/8	1/2	10 - 32	0.15	20
NMH7550	3/4	1/2	10 - 32	0.2	35
NMH1050	1	1/2	1/4 - 20	0.2	60
NMH1250	1-1/4	1/2	5/16 - 18	0.275	85
NMH1350	1-3/8	1/2	5/16 - 18	0.275	100

*This value is the recommended maximum holding power. Higher levels may be achieved, but are not advertised.



CHANNEL RAIL



CCR6213-(length)	Approximated 30 lbs. of holding power per inch.		
PART NO.	HEIGHT	WIDTH	LENGTH
CCR6213-12	5/8	1-3/8	12
CCR6213-18	5/8	1-3/8	18
CCR6213-24	5/8	1-3/8	24
CCR6213-36	5/8	1-3/8	36
CCR6213-48	5/8	1-3/8	48

CCR6223-(length)	Approximated 40 lbs. of holding power per inch.		
PART NO.	HEIGHT	WIDTH	LENGTH
CCR6223-12	5/8	2-3/8	12
CCR6223-18	5/8	2-3/8	18
CCR6223-24	5/8	2-3/8	24
CCR6223-36	5/8	2-3/8	36
CCR6223-48	5/8	2-3/8	48

* Custom lengths available

* Note: Not recommended for lifting. Inquire about Lift Magnets for lifting application.

CUP ASSEMBLIES



MODEL	DIAMETER	HEIGHT	HOLE	LIFTS*	WEIGHT
NMC2031A	2.0"	5/16"	3/16"	80 lbs.	.16 lbs.
NMC2031B	2.0"	5/16"	3/16"	125 lbs.	.19 lbs.
NMC2637	2-5/8"	3/8"	1/4"	200 lbs.	.44 lbs.
80c Maximum Operating Temperature					
*Holding force determined under ideal conditions, safety dictates a workload 1/2 of maximum.					

For technical assistance or to order

1-800-SUREMAG

900 S. Glaspie St.
Oxford, MI 48371
Ph: 248-628-3808
Fax: 248-628-3844

www.puritanmagnetics.com
Email: magnet@puritanmagnetics.com

Solutions to Your Magnetic Needs

